

# Solarium Options



## Electrical lifting unit




Electrical lifting unit for lifting the solarium. Including mounting kit, wall switch, electrical cable and connector cable. Max. lifting weight 50 kg. Max. lifting height 1,5 mtr.



## Winch system

Winch system for lifting the solarium manual. Including pullys, cable and mounting kit. Max. lifting weight 50kg.



## Steel angle support

Galvanized angle support for mounting the solarium to a vertical wall. Including mounting kit. Perfect when you don't have a roof or a high roof.



## Angled roof bracket Set

Galvanised brackets for mounting the solarium, potentially with an lifting unit, on an angled ceiling.



## Telescope bracket

Galvanized telescope support for mounting the solarium between 2 walls. Max. 3,5 metres between the walls. Including mounting kit.



## KY ML – side unit

The side units increases the heat to your horse, and particularly to the flanks of the horse. The side unit is adjustable across an angle of 45°. As a result of this, you are able to fully tailor the side units to your horse and according to your wishes.



INNOVATION - QUALITY - SERVICE

SOLARIUM **Solarium Options**

# Solarium Options



## Controlbox S-CB

Controlbox with ON/OFF-switch for IR-lights and ON/OFF-switch for the fans. Including powercable and connectorcable.



## Controlbox lifting unit S-CBE

Controlbox with ON/OFF-switch for IR-lights, ON/OFF-switch for the fans and a HIGHER/LOWER switch for the electrical lifting unit. Including powercable, cable to the lifting unit and connectorcable.



## Timercontrolbox S-CBT

Controlbox with LCD-timer for the IR-lights and ON/OFF-switch for the fans. By ordering several options, the switches for these options are including in this controlbox. Including powercable and connectorcable. Including potentially necessary cables for the options.



## All Weather controlbox AWCB

Controlbox with protection against dust and sprayingwater is resistant to the most severe conditions both outdoors and in damp rooms. Consider, for example, an operating environment where the controlbox needs to more tightly shut. The AWC-Box falls unthunder the IP55 protection class. The switches are behind plastic. Including powercable and connectorcable. Including potentially necessary cables and switches for the options.



## Controlbox Microtimer

Controlbox with microtimer for the IR-lights and ON/OFF-switch for the fans. Including powercable and connector cable. Including potentially needed switches and cables for the options.



Burenweg 50

NL-7621 GM

Borne

The Netherlands

+31 546 - 577305

E-mail [info@kylux.nl](mailto:info@kylux.nl)

[www.kylux.nl](http://www.kylux.nl)



# SOLARIUM OPTIONS